

PFP-PX-8M

Power Express module, connects up to 8 Powered Fiber Cables

Product Classification

Product Type	Power supply module
Regional Availability	Asia Australia/New Zealand EMEA Latin America North America

Body Features

Weight	1.13 kg 2.50 lb
--------	-------------------

Dimensions

Depth	322.33 mm 12.69 in
Height	43.69 mm 1.72 in
Width	87.38 mm 3.44 in

Electrical Specifications

Electrical Safety Standard	CSA C22.2 No. 60950-1-03
Electromagnetic Compatibility/Interference (EMC/EMI)	FCC-CFR, Part 15, sub-part B GR1089 Class A
Gauge Range	24–8 AWG
Input Current Range	0–20 A
Input Voltage Range	-42 to -60 Vdc
Output Voltage Range	-42 to 58 Vdc
Output Voltage, nominal	-57 Vdc
Total Output Power	100 W, per circuit

General Specifications

Brand	GE Industrial Solutions
-------	-------------------------

Industry Standards

Standards Compliance	ESD EN61000-4-2, Level 4
UL Listed	Yes

Packaging Features

Packaging Method	Box/Carton
Packaging Quantity	1

Usage Conditions

Operating Temperature Range	-40 – 65 °C
Relative Humidity (Operating)	5 – 95 % non-condensing

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	

Product Specifications

PFPPX-8M

ISO 9001:2008