CPCCC12

GigaSPEED XL® GS8E Ruggedized Plug, Coiled Strain Relief, Modular Patch Cord

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Portfolio SYSTIMAX®

Product TypeTwisted pair patch cord

Product Brand GigaSPEED XL®

Product Series CPC

Ordering Note Cords < 1 m are valid elements for use in a channel or as an equipment interconnect but

due to their limited length are not guaranteed to meet component compliance requirements that were developed to assess the quality of longer cords | Cords > 1 m are authorized for use in channels and are an effective standalone method used to connect active devices

General Specifications

ANSI/TIA Category 6

Cable Type U/UTP (unshielded)

Conductor TypeStrandedInterface, Connector ARJ45 plug

Interface Feature, connector A Ruggedized strain relief, coiled

Interface, Connector B RJ45 plug

Interface Feature, connector B Ruggedized strain relief, coiled

Jacket Color Black | Blue | Dark gray | Light

blue | Lilac | Orange | Purple | Red | Spring

green | Violet | White | Yellow

Pairs, quantity

Transmission Standards IEEE 802.3bt Type 4

Wiring T568B

Dimensions

Cable Assembly Length Range (m) 1 - 30

Cable Assembly Length Range (ft) 1 - 100

Diameter Over Jacket 5.97 mm | 0.235 in

Wiring Diagram



CPCCC12

	Connector A	Connector B
Position 1	White/Orange	White/Orange
Position 2	Orange	Orange
Position 3	Lt. Green	Lt. Green
Position 4	Blue	Blue
Position 5	Lt. Blue	Lt. Blue
Position 6	Green	Green
Position 7	Lt. Brown	Lt. Brown
Position 8	Brown	Brown

Electrical Specifications

dc Resistance, maximum 0.3 ohm

Material Specifications

Contact Plating Material Precious metals

Material Type Copper alloy | Polycarbonate

Mechanical Specifications

Plug Insertion Life, minimum 750 times

Plug Retention Force, minimum 133 N | 29.9 lbf

Environmental Specifications

Operating Temperature $-10 \,^{\circ}\text{C} \text{ to } +60 \,^{\circ}\text{C} \text{ (+14 }^{\circ}\text{F to } +140 \,^{\circ}\text{F)}$

Environmental SpaceNon-plenumFlammability RatingUL 94 V-0Safety StandardETL | cETL

Packaging and Weights

Packaging quantity 1

Regulatory Compliance/Certifications

Agency Classification



CPCCC12

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

