


## SYSTIMAX 360™ Evolve 24-port flat panel



### Product Classification

#### Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

#### Portfolio

SYSTIMAX®

#### Product Type

RJ45 patch panel

#### Product Brand

SYSTIMAX 360™

### General Specifications

#### ANSI/TIA Category

5e | 6 | 6A

#### Cable Type

Unshielded

#### Color

Cool gray

#### Modules, quantity

24

#### Panel Style

Straight

#### Rack Type

EIA 19 in

#### Rack Units

1

#### Total Ports, quantity

24

#### Wiring

T568A | T568B

### Dimensions

#### Height

44.45 mm | 1.75 in

#### Label Height

10.922 mm | 0.43 in

#### Width

482.6 mm | 19 in

#### Label Length

33.782 mm | 1.33 in

#### Depth

40.64 mm | 1.6 in

#### Depth, with cable management

170.18 mm | 6.7 in

#### Compatible Diameter Over Dielectric, maximum

1.168 mm | 0.046 in

# 760187187 | 360-E-MOD-1U-24

**Compatible Diameter Over Dielectric, minimum** 0.762 mm | 0.03 in

## Electrical Specifications

**Current Rating at Temperature** 1.5 A @ 20 °C | 1.5 A @ 68 °F

**Dielectric Withstand Voltage, RMS, conductive surface** 1,500 Vac @ 60 Hz

**Dielectric Withstand Voltage, RMS, contact-to-contact** 1,000 Vac @ 60 Hz

**Insulation Resistance, minimum** 500 MOhm

## Material Specifications

**Material Type** High-impact, flame retardant, thermoplastic | Powder-coated steel

## Environmental Specifications

**Operating Temperature** -10 °C to +60 °C (+14 °F to +140 °F)

**Storage Temperature** -40 °C to +70 °C (-40 °F to +158 °F)

**Relative Humidity** Up to 95%, non-condensing

**Flammability Rating** UL 94 V-0

**Safety Standard** UL | cUL

## Packaging and Weights

**Packaging quantity** 1

**Weight, net** 0.499 kg | 1.1 lb

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant

