

# FJWMPMPAD

---



Singlemode MPO (Female) to MPO (Female), InstaPATCH® 360 Pre-terminated Trunk Cable, 12-Fiber, Low Smoke Zero Halogen

## Product Classification

<b>Regional Availability</b>	Asia   Australia/New Zealand   Europe   Latin America   Middle East /Africa   North America
<b>Portfolio</b>	CommScope®
<b>Product Type</b>	Fiber trunk cable assembly
<b>Product Brand</b>	SYSTIMAX InstaPATCH® 360
<b>Ordering Note</b>	For lengths greater than 999 ft (304 m), orders must be in meters   Minimum length may vary based on cable configuration   Not available in the United States or Canada

## General Specifications

<b>Color, boot A</b>	Black
<b>Color, boot B</b>	Black
<b>Color, connector A</b>	Green
<b>Color, connector B</b>	Green
<b>Construction Type</b>	Stranded
<b>Fibers per Subunit, quantity</b>	12
<b>Furcation Color</b>	Yellow
<b>Interface, Connector A</b>	MPO-12/APC
<b>Interface, Connector B</b>	MPO-12/APC
<b>Jacket Color</b>	Yellow
<b>Total Fibers, quantity</b>	12


## Dimensions

<b>Breakout Length</b>	33 in
<b>Cable Assembly Length, minimum (ft)</b>	10
<b>Cable Assembly Length, maximum (ft)</b>	999

# FJWMPMPAD

<b>Cable Assembly Length, minimum (m)</b>	3
<b>Cable Assembly Length, maximum (m)</b>	999

## Ordering Tree



## Mechanical Specifications

<b>Cable Retention Strength, maximum</b>	11.24 lb @ 0 °   4.40 lb @ 90 °
--	---------------------------------

## Optical Specifications

<b>Fiber Mode</b>	Singlemode
<b>Fiber Type</b>	G.652.D   G.657.A1, TeraSPEED®

## Environmental Specifications

<b>Operating Temperature</b>	-10 °C to +60 °C (+14 °F to +140 °F)
<b>Environmental Space</b>	Dual Rated LSZH/Riser

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant



## Included Products

# FJWMPMPAD

---

760050328 — TeraSPEED® Low Smoke Zero Halogen Riser MPO Trunk Cable, 12 fiber  
N-012-MP-8W-F12YL/D

860366137 — MPO12, STANDARD LOSS, FEMALE, SM, GREEN, 3mm