



760187203 | 360-E-ANG-MOD-1U-24  
**SYSTIMAX 360™ Evolve 24-port angled panel**

## Dimensions

Depth	139.70 mm   5.50 in
Depth, with cable management	10.60 in
Diameter Over Dielectric, maximum	1.168 mm   0.046 in
Diameter Over Dielectric, minimum	0.762 mm   0.030 in
Height	44.45 mm   1.75 in
Weight	0.59 kg   1.30 lb
Width	482.60 mm   19.00 in

## Electrical Specifications

ANSI/TIA Category	5e   6   6A
Current Rating	1.5 A @ 20 °C 1.5 A @ 68 °F
Dielectric Withstand Voltage, RMS, conductive surface	1500 Vac @ 60 Hz
Dielectric Withstand Voltage, RMS, contact-to-contact	1000 Vac @ 60 Hz
Insulation Resistance, minimum	500 MOhm

## Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Relative Humidity	Up to 95%, non-condensing
Safety Standard	cUL   UL
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

## General Specifications

Total Ports, quantity	24
Cable Type	U/UTP (unshielded)
Product Type	Panel
Brand	CommScope®
Color	Cool gray
Label Height	0.43 in
Label Length	1.33 in
Modules, quantity	24
Package Quantity	1
Rack Type	EIA 19 in
Rack Units	1

## Mechanical Specifications

760187203 | 360-E-ANG-MOD-1U-24

Panel Style	Angled
Material Type	High-impact, flame retardant, thermoplastic   Powder-coated steel
Wiring	T568A   T568B

## Regulatory Compliance/Certifications

### Agency

RoHS 2011/65/EU

ISO 9001:2008

### Classification