

5-558530-3

RJ45 Plug, category 5e, 8-position, unshielded, standard latch

OBSOLETE

Replaced By

6-569278-3
MP-5EU-1

Modular Plug Kit, category 5e, 8P/8C, unshielded, 4.8 – 5.6 mm max cable jack OD, 8-position, 100/bag

Product Classification

Portfolio	NETCONNECT®
Product Type	Modular plug
Regional Availability	Asia Australia/New Zealand EMEA Latin America North America

Body Features

Conductor Type	Stranded
----------------	----------

Configuration Features

Number of Positions	8
Keyed	No

Contact Features

Contact Base Material	Phosphor bronze
Number of Contacts Loaded	8

Dimensions

Cable Jacket Outside Diameter Range	0.19–0.22 in 4.83–5.59 mm
Conductor Wire Size	26–24 AWG
Insulated Conductor Outside Diameter	0.035–0.039 in 0.89–0.99 mm

Housing Features

Housing Material	Glass filled polycarbonate
------------------	----------------------------

Industry Standards

Standards Compliance	UL 94 V-2
----------------------	-----------

Packaging Features

Packaging Quantity	100
--------------------	-----

Product Type Features

Performance Category	Category 5e
Cable Style	Round
Connector Style	Plug

Product Specifications

5-558530-3

Latch Style	Standard
Shielded	No