


1-1933882-8 | C/A MPLUG CAT6A XG SL SHLD BLU



Body Features

Color	Blue
Cable Construction	PVC stranded
Conductor Material	Tinned copper
Shield Style	F/UTP

Configuration Features

Configuration	Double-ended
Keyed	No
Number of Positions	4-pair
Number of Power Positions	0
Wiring Pattern	T568B

Dimensions

Cable Assembly Length	18 ft 5.48 m
Length	5.490 m 18.012 ft
Overall Outside Cable Diameter	6.000 mm 0.236 in
Wire Size (CMA)	.129 mm ² 26 AWG

Industry Standards

Flammability Rating	Non-Plenum (CM Rated)
IEEE 1394	No

Operation/Application

Halogen Free	No
--------------	----

Other

Comment	North America has a corresponding part available under the TCPC-6ARFVB numbering scheme.
---------	------------------------------------------------------------------------------------------

Packaging Features

Packaging Method	Bag
------------------	-----

Product Availability

Region	Asia
--------	------

Product Type Features

1-1933882-8 | C/A MPLUG CAT6A XG SL SHLD BLU

Product Type	Cable Assembly
Assembly Type	Shielded Modular Plug to Shielded Modular Plug
Boot	With
Cable Assembly Category	Industry Standard
Cable Assembly Type	Shielded Modular Plug
Connector Type (End A)	Plug
Connector Type (End B)	Plug
Performance Category	Category 6A
Product Designation	Patch Cord
Shielded	Yes

Usage Conditions

Operating Temperature Range -20 – 60 °C | -4 – 140 °F
Storage Temperature -20 – 80 °C | -4 – 176 °F

Regulatory Compliance/Certifications

Agency
RoHS 2011/65/EU

Classification
Compliant