

Fiber Optic Patch Cord, OM4, LC/LC Duplex, 1.8mm, LSZH & OFNR, Aqua

Product Classification

Regional Availability

Asia | Australia/New Zealand | China | India

Portfolio CommScope®

Product Type Fiber patch cord, duplex

General Specifications

Color, boot AAquaColor, boot BAquaColor, connector ABeigeColor, connector BBeigeConnector A, quantity2Connector B, quantity2

 Interface, Connector A
 LC/UPC

 Interface, Connector B
 LC/UPC

 Jacket Color
 Aqua

Polarity Pairs, flipped


Total Fibers, quantity

Dimensions

Diameter Over Jacket 1.8 mm | 0.071 in

Ordering Tree





Mechanical Specifications

Cable Retention Strength, maximum 11.24 lb @ 0 °

Optical Specifications

Fiber Mode Multimode

Fiber Type OM4, LazrSPEED®

 Insertion Loss, maximum
 0.3 dB

 Return Loss, minimum
 20 dB

Environmental Specifications

Operating Temperature $-10 \,^{\circ}\text{C}$ to $+60 \,^{\circ}\text{C}$ (+14 $^{\circ}\text{F}$ to +140 $^{\circ}\text{F}$)

Environmental Space Dual Rated LSZH/Riser

Qualification Standards | IEC 60332-1 | IEC 60332-3 | IEC 60754 | IEC 61034

Packaging and Weights

Packaging quantity 1

